

Guangzhou Aanpire Electronics Corporation Limited

Addr: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China
 Tel: +86-20-8985 1135 | Fax: +86-20-8985 1135 | Email: sales@aanpire.com



Main Specification:

- Item: AP-4125**
- Metal bullet IP camera
 - 3.6mm fixed lens (2.8mm optional)
 - IR Leds & range: 12MIL*36PCS; 30M
 - Compression:H.265+/H.265/H.264
 - Resolution: 1080P/3MP/5MP

| | | | | | | |
|---------------------|--|-------------|-------------|-------------|---------------------------|-------------|
| Model No. | AP-4125322 | AP-4125323 | AP-4125324 | AP-4125325 | AP-4125332 | AP-4125352 |
| Image Sensor | SC2235 | SC2236 | IMX307 | IMX323 | AR0330 | OV5300 |
| Processor | MSC313E | HI3516EV100 | HI3516EV100 | HI3516EV100 | HI3516CV300 | HI3516D |
| Lens Megapixels | 3MP | 3MP | 3MP | 3MP | 4MP | 6MP |
| Min Illumination | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode | | | | | |
| Lens | 3.6mm @F2.0, (2.8mm optional) | | | | | |
| Night Vision | 12MILx36PCS IR LED; 30M | | | | | |
| IR control | Under 10 Lux By CDS (Day&night auto switch) | | | | | |
| S/N Ratio | ≥52dB | | | | | |
| Main Profile | H.265+/H.265/ H.264 | | | | | |
| Resolution | 1080P | 1080P | 1080P | 1080P | 3MP | 5MP |
| Frame rate | 1080P/20fps | 1080P/20fps | 1080P/20fps | 1080P/20fps | 3MP/15fps, 1080P/25fps | 5.0MP/20fps |
| Bit Rate | CBR/ VBR , output bit rate range: 0.1Mbps~8Mbps | | | | | |
| Picture Adjustment | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) | | | | | |
| Motion Detection | Motion detection, video loss, video block, etc | | | | | |
| Alarm action | image upload via Email/FTP server | | | | | |
| Ethernet | 1*10/100Mbps Ethernet port, RJ45 port | | | | | |
| Recording Mode | 3 Rectangular Zone | | | | | |
| Privacy Masking | Privacy Masking | | | | | |
| Network Protocal | TCP/IP, HTTP, TCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPnP, RTSP, P2P,etc | | | | | |
| Control Protocal | Onvif 2.4 | | | | | |
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari | | | | | |
| Smart Phone | iPhone, iPad, Android, Android Pad | | | | | |
| P2P | Yes,Support QR Code | | | | | |
| POE | Support | | | | | |
| POE protocal | IEEE802.3af (≤15.3w) supported | | | | | |
| WIFI | N/A | | | | | |
| Micro SD | N/A | | | | | |
| Language | Multi language | | | | | |
| Housing | Metal bullet,IP66 waterproof | | | | | |
| Rated Voltage | DC12V±10%, 700mA | | | | | |
| Power consumption | 6.0w (IR on) | | | | | |
| Working Environment | Temperature -20° to 70°, Humidity 90% | | | | | |
| Dimension(L*W*H) | 200 (W) x70 (H) x65 (D) mm | | | | | |
| Gross Weight | 700g | | | | | |