



Main Specification:

- Item: AP-41504**
- Metal Bullet IP camera
 - 2.8-12mm Manual Zoom Lens
 - IR Leds & range: 42MIL*2PCS; 40M
 - Compression:H.265+/H.265/H.264
 - Resolution: 1080P/3MP/4MP/5MP

| | | | | | | | | |
|---------------------|--|-------------|-------------|-------------|---------------------------|-------------|-----------------|-----------------|
| Model No. | AP-4150422 | AP-4150423 | AP-4150424 | AP-4150425 | AP-4150432 | AP-4150452 | AP-4150421 | AP-4150441 |
| Image Sensor | SC2235 | SC2236 | IMX307 | IMX323 | AR0330 | OV5300 | SONY222 | OV4689 |
| Processor | MSC313E | HI3516EV100 | HI3516EV100 | HI3516EV100 | HI3516CV300 | HI3516D | HI3516C | HI3516D |
| Lens Megapixel | 3MP | 3MP | 3MP | 3MP | 4MP | 6MP | 2MP(Auto focus) | 4MP(Auto focus) |
| Min Illumination | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode | | | | | | | |
| Lens | 2.8-12mm Manual Zoom Lens | | | | | | | |
| Night Vision | 42MILx2PCS IR LED; 40M | | | | | | | |
| IR control | Under 10 Lux By CDS (Day&night auto switch) | | | | | | | |
| S/N Ratio | ≥52dB | | | | | | | |
| Main Profile | H.265+/H.265/ H.264 | | | | | | | |
| Resolution | 1080P | 1080P | 1080P | 1080P | 3MP | 5MP | 2MP | 4MP |
| Frame rate | 1080P/20fps | 1080P/20fps | 1080P/20fps | 1080P/20fps | 3MP/15fps, 1080P/25fps | 5.0MP/20fps | 1080P/30fps | 4MP/20fps |
| Bit Rate | CBR/ VBR , output bit rate range: 0.1Mbps~8Mbps | | | | | | | |
| Picture Adjustment | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) | | | | | | | |
| Motion Detection | Motion detection, video loss, video block, etc | | | | | | | |
| Alarm action | image upload via Email/FTP server | | | | | | | |
| Ethernet | 1*10/100Mbps Ethernet port, RJ45 port | | | | | | | |
| Recording Mode | 3 Rectangular Zone | | | | | | | |
| Privacy Masking | Privacy Masking | | | | | | | |
| Network Protocol | TCP/IP, HTTP, TCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPnP, RTSP, P2P,etc | | | | | | | |
| Control Protocol | Onvif 2.4 | | | | | | | |
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari | | | | | | | |
| Smart Phone | iPhone, iPad, Android, Android Pad | | | | | | | |
| P2P | Yes,Support QR Code | | | | | | | |
| POE | Support | | | | | | | |
| POE protocol | IEEE802.3af (≤15.3w) supported | | | | | | | |
| WIFI | N/A | | | | | | | |
| Micro SD | N/A | | | | | | | |
| Language | Multi language | | | | | | | |
| Housing | Metal Bullet;IP66 warter proof | | | | | | | |
| Rated Voltage | DC12V±10%, 700mA | | | | | | | |
| Power consumption | 6.0w (IR on) | | | | | | | |
| Working Environment | Temperature -20° to 70°, Humidity 90% | | | | | | | |
| Dimension(L*W*H) | 219. 5 (W) x101. 5 (H) x97. 5 (D) mm | | | | | | | |
| Gross Weight | 1.4kg | | | | | | | |