

**Guangzhou Aanpire Electronics Corporation**

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China  
 Tel: +86-20-8985 1135 | Fax: +86-20-8985 1135 | Email: sales@aanpire.com



**Main Specification:**

**Item: AP-41536**

- Metal Bullet IP camera
- 2.8-12mm Manual Zoom Lens
- IR Leds & range: 12MIL\*72PCS; 60M
- Compression:H.265+/H.265/H.264
- Resolution: 1080P/3MP/4MP/5MP

Model No.	AP-4153622	AP-4153623	AP-4153624	AP-4153625	AP-4153632	AP-4153652	AP-4153621	AP-4153641
Image Sensor	SC2235	SC2236	IMX307	IMX323	AR0330	OV5300	SONY222	OV4689
Processor	MSC313E	HI3516EV100	HI3516EV100	HI3516EV100	HI3516CV300	HI3516D	HI3516C	HI3516D
Lens Megapixel	3MP	3MP	3MP	3MP	4MP	6MP	2MP(Auto focus)	4MP(Auto focus)
Min Illumination	0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode							
Lens	2.8-12mm Manual Zoom Lens							
Night Vision	12MILx72PCS IR LED; 60M							
IR control	Under 10 Lux By CDS (Day&night auto switch)							
S/N Ratio	≥52dB							
Main Profile	H.265+/H.265/ H.264							
Resolution	1080P	1080P	1080P	1080P	3MP	5MP	2MP	4MP
Frame rate	1080P/20fps	1080P/20fps	1080P/20fps	1080P/20fps	3MP/15fps, 1080P/25fps	5.0MP/20fps	1080P/30fps	4MP/20fps
Bit Rate	CBR/ VBR , output bit rate range: 0.1Mbps~8Mbps							
Picture Adjustment	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)							
Motion Detection	Motion detection, video loss, video block, etc							
Alarm action	image upload via Email/FTP server							
Ethernet	1*10/100Mbps Ethernet port, RJ45 port							
Recording Mode	3 Rectangular Zone							
Privacy Masking	Privacy Masking							
Network Protocol	TCP/IP, HTTP, TCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPnP, RTSP, P2P,etc							
Control Protocol	Onvif 2.4							
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari							
Smart Phone	iPhone, iPad, Android, Android Pad							
P2P	Yes,Support QR Code							
POE	Support							
POE protocol	IEEE802.3af (≤15.3w) supported							
WIFI	N/A							
Micro SD	N/A							
Language	Multi language							
Housing	Metal Bullet;IP66 warter proof							
Rated Voltage	DC12V±10%, 700mA							
Power consumption	6.0w (IR on)							
Working Environment	Temperature -20° to 70°, Humidity 90%							
Dimension(L*W*H)	240 (W) x186 (H) x100 (D) mm							
Gross Weight	1.7kg							