

**Guangzhou Aanpire Electronics Corporation Limited**

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China  
 Tel: +86-20-8985 1135 | Email: sales@aanpire.com  
 Website: http://www.aanpire.com/



**Features:**

- Item : AP-3159
- Indoor Metal Dome Housing
- AHD/CVI/TVI/CVBS 4 IN 1
- 3.6mm Fixed Lens
- IR LED:14MIL\*18PCS;IR Distance:20M
- 1MP/2MP/3MP/4MP/5MP

| Model No.           | AP-3159212  | AP-3159222  | AP-3159223     | AP-3159224       | AP-3159242     |     |  |
|---------------------|---|-------------|----------------|------------------|----------------|-----|--|
| Solution            | H42+HDI8901   | F33+FH8536H | IMX323+FH8536H | IMX307+NVP2441H  | OV4689+FH8538M |     |  |
| Video output mode   | AHD/CVI/TVI/CVBS 4 in 1 ; AHD default                 |             |                |                  |                |     |  |
| Resolutions         | 720P  | 1080P       | 1080P          | 1080P(STARLIGHT) | 4MP            |     |  |
| TV System           | PAL/ NTSC   |             |                |                  |                |     |  |
| Min Illumination    | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode |             |                |                  |                |     |  |
| Lens                | 3.6mm fixed lens                                      |             |                |                  |                |     |  |
| Night Vision        | SMT IR LED: 14MIL*18PCS, IR Distance up to 20 meters  |             |                |                  |                |     |  |
| IR control          | ICR Auto Detect (Day&night auto switch)               |             |                |                  |                |     |  |
| IR status           | Under 10 Lux by CDS                                   |             |                |                  |                |     |  |
| Sync System         | Internal  |             |                |                  |                |     |  |
| S/N Ratio           | ≥50dB   |             |                |                  |                |     |  |
| Electronic Shutter  | 1/25s~1/50,000s , 1/30s~1/60,000s                     |             |                |                  |                |     |  |
| OSD Menu            | OSD Optional  |             |                | with OSD         |                |     |  |
| UTC                 | with UTC  |             |                |                  |                |     |  |
| WDR                 | Support   |             |                |                  |                |     |  |
| Noise Reduction     | D NR  | 3D NR       | 3D NR          | D NR             | DNR            | DNR |  |
| Housing             | Metal Indoor Dome                                     |             |                |                  |                |     |  |
| Rated Voltage       | DC12V±10%   |             |                |                  |                |     |  |
| Power consumption   | 4.0w (IR on)  |             |                |                  |                |     |  |
| Working Environment | Temperature -20° to 70°, Humidity 90%                 |             |                |                  |                |     |  |
| Dimension(L*W*H)    | ∅ 108 x 69 (H) mm                                     |             |                |                  |                |     |  |
| Gross Weight        | 450g  |             |                |                  |                |     |  |