

Guangzhou Aanpire Electronics Corporation Limited

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China
 Tel: +86-20-8985 1135 | Email: sales@aanpire.com
 Website: http://www.aanpire.com/



Features:

- Item : AP-3153
- Metal Bullet Housing
- AHD/CVI/TVI/CVBS 4 IN 1
- 2.8-12mm varifocal lens
- IR LED:12MIL*42PCS;IR Distance:40M
- 1MP/2MP/3MP/4MP/5MP

| Model No. | AP-3153412 | AP-3153422 | AP-3153423 | AP-3153424 | AP-3153442 | AP-3153452 | AP-3153421 |
|---------------------|---|-------------|----------------|------------------|----------------|----------------|-----------------|
| Solution | H42+HD18901 | F33+FH8536H | IMX323+FH8536H | IMX307+NVP2441H | OV4689+FH8538M | IMX326+FH8538M | IMX323+NVP2440 |
| Video output mode | AHD/CVI/TVI/CVBS 4 in 1 ; AHD default | | | | | | |
| Resolutions | 720P | 1080P | 1080P | 1080P(Starlight) | 4MP | 5MP | 2MP(Auto focus) |
| TV System | PAL/ NTSC | | | | | | |
| Min Illumination | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode | | | | | | |
| Lens | 2.8-12mm varifocal lens | | | | | | |
| Night Vision | SMT IR LED: 12MIL*42PCS, IR Distance up to 40 meters | | | | | | |
| IR control | ICR Auto Detect (Day&night auto switch) | | | | | | |
| IR status | Under 10 Lux by CDS | | | | | | |
| Sync System | Internal | | | | | | |
| S/N Ratio | ≥50dB | | | | | | |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s | | | | | | |
| OSD Menu | OSD Optional | | | with OSD | | | |
| UTC | with UTC | | | | | | |
| WDR | Support | | | | | | |
| Noise Reduction | D NR | 3D NR | 3D NR | D NR | DNR | DNR | DNR |
| Housing | Metal BULLET | | | | | | |
| Rated Voltage | DC12V±10% | | | | | | |
| Power consumption | 4.0w (IR on) | | | | | | |
| Working Environment | Temperature -20° to 70°, Humidity 90% | | | | | | |
| Dimension(L*W*H) | 200 (W) x171 (H) x83 (D) mm | | | | | | |
| Gross Weight | 1.4kg | | | | | | |