

**Guangzhou Aanpire Electronics Corporation Limited**

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China  
 Tel: +86-20-8985 1135 | Email: sales@aanpire.com  
 Website: http://www.aanpire.com/



**Features:**



- Item : AP-31463
- Metal Bullet Housing
- AHD/CVI/TVI/CVBS 4 IN 1
- 3.6mm Fixed Lens
- IR LED:5MIL\*36PCS;IR Distance:30M
- 1MP/2MP/3MP/4MP/5MP

| Model No.           | AP-3146312  | AP-3146322  | AP-3146323     |          | AP-3146342     | AP-3146352     |     |
|---------------------|---|-------------|----------------|----------|----------------|----------------|-----|
| Solution            | H42+HDI8901   | F33+FH8536H | IMX323+FH8536H |          | OV4689+FH8538M | IMX326+FH8538M |     |
| Video output mode   | AHD/CVI/TVI/CVBS 4 in 1 ; AHD default                 |             |                |          |                |                |     |
| Resolutions         | 720P  | 1080P       | 1080P          |          | 4MP            | 5MP            |     |
| TV System           | PAL/ NTSC   |             |                |          |                |                |     |
| Min Illumination    | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode |             |                |          |                |                |     |
| Lens                | 3.6mm fixed lens                                      |             |                |          |                |                |     |
| Night Vision        | SMT IR LED: 5MIL*36PCS, IR Distance up to 30 meters   |             |                |          |                |                |     |
| IR control          | ICR Auto Detect (Day&night auto switch)               |             |                |          |                |                |     |
| IR status           | Under 10 Lux by CDS                                   |             |                |          |                |                |     |
| Sync System         | Internal  |             |                |          |                |                |     |
| S/N Ratio           | ≥50dB   |             |                |          |                |                |     |
| Electronic Shutter  | 1/25s~1/50,000s , 1/30s~1/60,000s                     |             |                |          |                |                |     |
| OSD Menu            | OSD Optional  |             |                | with OSD |                |                |     |
| UTC                 | with UTC  |             |                |          |                |                |     |
| WDR                 | Support   |             |                |          |                |                |     |
| Noise Reduction     | D NR  | 3D NR       | 3D NR          | D NR     | DNR            | DNR            | DNR |
| Housing             | Metal BULLET  |             |                |          |                |                |     |
| Rated Voltage       | DC12V±10%   |             |                |          |                |                |     |
| Power consumption   | 4.0w (IR on)  |             |                |          |                |                |     |
| Working Environment | Temperature -20° to 70°, Humidity 90%                 |             |                |          |                |                |     |
| Dimension(L*W*H)    | 200 (W) x67 (H) x66 (D) mm                            |             |                |          |                |                |     |
| Gross Weight        | 700g  |             |                |          |                |                |     |