

Guangzhou Aanpire Electronics Corporation Limited

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China
 Tel: +86-20-8985 1135 | Email: sales@aanpire.com
 Website: http://www.aanpire.com/



Features:



- ONVIF 2.4 compatible; P2P
- Optional: Alarm, Audio, SD Card slot
- Compatible with HIKVISION ,DAHUA, XM NVR etc
- Compatible with Milestone and AXON platform
- 4.5" high speed, IP66
- 2MP/4MP optional
- 10X/20X/33X optional

| Model No. | AP-4241021 | AP-4241041 | |
|-------------------------------|---|----------------------|--|
| Image Sensor | 1/3" CMOS Sony IMX323 | 1/3" CMOS 4MP OV4689 | |
| Resolution | 1080P | 4MP | |
| Lens | 10X f=5.1mm(W) ~ 51mm(T) | | |
| Iris | F1.6-F1.8 | | |
| Min. illumination | Color: 0.1Lux\ B/W: 0.01Lux | | |
| FOV | 4.2°~68.5° | | |
| D/N | IR-CUT | | |
| AGC | Auto/manual | | |
| WB | Auto/manual/indoor/outdoor | | |
| Shutter | 1/2 - 1/20,000s | | |
| S/N Ratio | ≥50dB | | |
| Communication Protocol | TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P | | |
| Software Control | IE, CMS, Management Platform | | |
| Storage(optional) | SD card | | |
| Audio and alarm(optional) | alternative | | |
| Mobile View | Android, iphone | | |
| Horizontal Rotation Speed | Pan: 0~480°/s , Tilt: 0~240°/s | | |
| Horizontal Rotation Range | Horizontal 180°, Vertical 93° | | |
| Pan and Tilt position display | Support | | |
| Auto Flip | Horizontal 180°, Vertical 93° | | |
| Ratio Speed | Support | | |
| Auto Control IR LED | PWM | | |
| IR Illumination On | 1-15 grades selectable | | |
| IR distance | up to 80 meters | | |
| 360° Scan | 1-64 grades setting available | | |
| A-B Scan | User programmable | | |
| A-B Scan Speed | 1-64 grades setting available | | |
| PWR on Action | Memory/Tour 1/360° scan/A-B scan/Park 1/None | | |
| Park Mode | Tour 1/360° scan/A-B scan/Park 1/None | | |
| Park Time | 1-60mins setting available | | |
| Dwell Preset | 1-60s interval available | | |
| Preset Points | 220 | | |
| Go to Preset Speed | 1-64 grades available | | |
| Guard Tours | 3 groups | | |
| Guard Points | Max.16 points, dwell time user selectable | | |
| Alarm | 1/1 (optional) | | |
| Timing Run | Built-in high-precision RTC clock, support time management | | |
| OSD Menu | Multi-language | | |
| Communication Protocol | Pelco-D, Pelco-P | | |
| Baud Rate | 1200/2400/4800/9600bps(Default is 9600bps) | | |
| Privacy Mask | Support (according to camera module type) | | |
| Waterproof | IP66 | | |
| Operating Temperature | Indoor: 0°~ +40° Outdoor: -40°~ +60° | | |
| Operating Humidity | ≤95% Non Condensing | | |
| Heater & Blower | Auto temperature control | | |
| Power | DC12V 3A | | |
| Lightning Protection | Transient voltage 6000V | | |