

HD-IP MINI PTZ BULLET:AP-4210



- * Support audio, POE (optional)
- *ONVIF2.4;Support P2P function
- *Support H.264 (H.265)compression
- *Pan/Tilt/Zoom, A-B scan, tour available
- * Compatible with HIKVISION ,DAHUA, XM NVR
- *Compatible with Milestone, NUUO and AXXON platform

Specification				
Camera				
Sensor	Mstat313e+2235(2.0MP)	Mstat316DM+OV4689(4.0MP)	1/3" CMOS 2MP Sony323	1/3" CMOS 5MP AR0521
Output pixel	1080p/20fps	2560*1440/20fps	1920x1080/30fps 1920x1080/25fps	2592x1944@15fps 2592x1520@22fps
Lens	4mm/2.8-12mm			
BLC	Support			
AGC	Auto/manual			
WB	Auto/manual/indoor/outdoor			
S/N Ratio	>50dB			
Dome				
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P			
Software Control	IE, CMS, Management Platform			
Video compression	H.264/H.265/M-JPEG			
Audio compression	G711, PCM			
Mobile View(optional)	Android iPhone			
Rotation Range	Pan: 0°~160° , Tilt: 0°~55°			
Rotation Speed	Pan: 0~25°/s , Tilt: 0~20°/s			
Auto Flip	Support			
Preset Points	220pcs presets (dwell time 01-60s interval available)			
Guard Tours	3 groups (each group 16 preset, dwell time and speed selectable)			
AB scan range	Support, 0-160°			
AB scan speed	1-9 grades			
Operating temperature	-30℃~+60℃			
Operation menu	English			
Auto Control IR LED	PWM			
Consumption	≤10W			
Lightning Protection	Transient voltage 6000V			
Related validation	IP66,CE,FCC,RoHs			
Package Box	205*115*135mm			
Weight	N: 0.55KG/ G: 0.67KG			
IR parameters				
Auto Control IR LED	PWM			
IR distance	up to 50 meters			
LEDs	6 PCS Array 30MII LED			

