

Guangzhou Aanpire Electronics Corporation Limited

Add: #7 Dalinshan Road, Tianhe District, Guangzhou-510630, China
 Tel: +86-20-8985 1135 | Email: sales@aanpire.com
 Website: http://www.aanpire.com/



Features:

- 4.5", IP66 Metal outdoor Speed Dome Housing
- 3 IN 1 Medium speed dome with OSD
- AHD/TVI/CVI/CVBS selectable
- Resolution: 2MP (1920*1080)
- Pan, Tilt, Zoom
- 6PCS Array IR LED, Night Vision 50meters

Model No.	AP-3221821
Image Sensor	1/3" 2.0MP CMOS Sony IMX323
Lens	Lens:5.35mm~93.6mm;18X optical zoom
IR LEDs	6PCS Array IR LEDs, night vision Up to 50 meters
IR control	PWM, (Day&night auto switch)
Interface	3-in-1 , COAXIAL CABLE, AHD/TVI/CVI/CVBS selectable
S/N Ratio	≥50dB
Communication mode	RS485 (+/-) / coaxial cable
Resolution	2MP (1920*1080)
Pan Rotation	0°~360°, 0~80°/s
Tilt Rotation	0°~93°, 0~40°/s
Auto Flip	Support
Ratio Speed	Support
A-B Scan	User programmable (scan speed 1-64 levels setting available)
Preset Points	220pcs preset(Dwell time 01-60s interval available)
Guard Tours & points	3 groups (Max.16 points, dwell time user selectable)
Picture Adjustment	Contrast, Brightness, saturation,White Balance, BLC, AGC, D-WDR
Motion Detection	Motion detection, video loss, video block, etc
Alarm action	image upload via Email/FTP server
Storage Mode	client storage, NVS, NVR
Micro SD	N/A
Housing	4.5" IP66 Weatherproof Housing, with Wall mount bracket
Cable built-in bracket	Yes
Rated Voltage	DC12V ±5%, 4A
Power consumption	≤ 25W (IR on)
Heater & Blower	Option
Lightning Protection	Transient voltage 6000V
Working Environment	Indoor: 0°~ +40° Outdoor: -40°~ +60°, ≤90% Non Condensing
Dimension(L*W*H)	
Gross Weight	
Monitoring	Remote monitoring, iOS / Android/ MAC app supported